

## APC 系列橱窗式换气扇 Window Type Exhaust Fan

换气扇采用全新抗静电, 抗老化工程塑料制造, 结构紧凑, 安全平稳牢固。采用优质罩板电机, 运行平稳, 风量。适用于会客室、办公室、民用住宅等。

Material: made of antistatic and anti-aging ABS plastic.  
Structure: compact, safe, stable and firm.  
Application: suitable for ventilation in sitting room, office, shopping mall, building and etc.

机号 Model(Nº)	规格 Size	功率 Power(W)	电压 Voltage(V)	流量 Volume(m³/h)	噪声 Noise dB(A)	适用面积 Usable Area(m²)
APC10-F1	4寸(方形风压)	12	220	100	40	4~8
APC15-F1	6寸(方形风压)	17	220	200	42	8~16
APC20-F1	8寸(方形风压)	25	220	300	45	12~24
APC10-C1	4寸(方形超薄)	15	220	100	40	4~8
APC15-C1	6寸(方形超薄)	20	220	200	42	8~16



方形超薄 Super thin square type  
方形风压 Square Type

## BPT 系列超静音天花板管道换气扇 Ceiling Mounted Ventilation Fan

通过优化风道设计, 配合高效率、长寿命滚珠轴承电机。使产品的能效达到最优化, 适用于不间断换气。广泛用于宾馆酒店、百货商场、娱乐场所及民用住宅通风换气。

Optimal air duct design, Motor with high-efficiency & long-life ball bearing, Optimized efficiency; suitable for continuous ventilation, Application: Ventilation for hotels, shopping malls, places of entertainment and buildings.



半金属系列 Semimetal Series  
全塑系列 Plastic Series

系列 Series	机号 Model(Nº)	功率 Power(W)	电压 Voltage(V)	流量 Volume(m³/h)	静压 Static pressure(Pa)	适用面积 Usable Area(m²)	噪声 Noise dB(A)
全塑系列 Plastic Series	BPT10-21S	20	220	150	100	6~12	33
	BPT10-24SL	22	220	200	110	8~16	35
	BPT10-24SH	25	220	250	120	10~20	39
	BPT15-27SL	35	220	300	120	12~24	33
	BPT15-27SH	39	220	380	150	15~30	37
半金属系列 Semimetal Series	BPT15-32S	40/35	220	550/450	150/120	18~44	42/37
	BPT10-21J	20	220	150	100	6~12	33
	BPT10-24JL	22	220	200	110	8~16	35
	BPT10-24JH	25	220	250	120	10~20	39
	BPT15-27JL	35	220	300	120	12~24	33
	BPT15-27JH	39	220	380	150	15~30	37
	BPT15-32J	40/35	220	550/450	150/120	18~44	42/37

## APT 系列全塑天花板式换气扇 Plastic Ceiling Mounted Ventilation fan

采用全新抗静电, 抗老化工程塑料制造, 选用优质滚珠轴承电机, 运转噪音低, 大风量寿命长久, 实现超静音。适用于会客室、办公室、商场、民用住宅等。

Material: made of antistatic and anti-aging ABS plastic.  
Motor: good quality ball bearing, low noise, large air volume, long service life, super quiet.  
Application: suitable for Ventilation in sitting room, office, shopping mall, building and etc.



机号 Model(Nº)	规格 Size	功率 Power(W)	电压 Voltage(V)	流量 Volume(m³/h)	噪声 Noise dB(A)	适用面积 Usable Area(m²)
APT15-S	6寸	24	220	300	40	12~24
APT20-S	8寸	28	220	550	41	22~44
APT25-S	10寸	36	220	900	43	36~72
APT30-S	12寸	48	220	1200	46	48~96

## APB/ASB 系列全塑百叶窗换气扇 Plastic Exhaust Fan with Shutter

采用全新抗静电, 抗老化工程塑料制造, 选用优质滚珠轴承电机, 运转噪音低, 大风量寿命长久, 实现超静音。适用于会客室、办公室、商场、民用住宅等。

Material: made of antistatic and anti-aging ABS plastic.  
Motor: good quality ball bearing, low noise, large air volume, long service life, super quiet.  
Application: Suitable for ventilation in sitting room office, shopping mall, building and etc.

系列 Series	机号 Model(Nº)	规格 Size	功率 Power(W)	电压 Voltage(V)	流量 Volume(m³/h)	噪声 Noise dB(A)	适用面积 Usable Area(m²)
标准型(滚珠轴承) Standard Type(Ball Bearing)	APB20-S1	8寸(单向无网)	28	220	550	41	22~44
	APB25-S1	10寸(单向无网)	36	220	900	42	36~72
	APB30-S1	12寸(单向无网)	48	220	1200	46	48~96
	ASB20-S1	8寸(双向无网)	28	220	550	41	22~44
	ASB25-S1	10寸(双向无网)	36	220	900	42	36~72
	ASB30-S1	12寸(双向无网)	48	220	1200	46	48~96
	APB20-S2	8寸(双速无网)	28/23	220	550/400	41/38	22~44
	APB25-S2	10寸(双速无网)	36/31	220	900/650	42/39	36~72
豪华型(滚珠轴承) Luxury Type(Ball Bearing)	APB30-S2	12寸(双速无网)	48/42	220	1200/900	46/41	48~96
	APB15-SH1	6寸(单向带网)	24	220	300	39	12~24
	APB20-SH1	8寸(单向带网)	28	220	550	41	22~44
	APB25-SH1	10寸(单向带网)	36	220	900	42	36~72
	APB30-SH1	12寸(单向带网)	48	220	1200	46	48~96
	ASB20-SH1	8寸(双向带网)	28	220	550	41	22~44
	ASB25-SH1	10寸(双向带网)	36	220	900	42	36~72
	ASB30-SH1	12寸(双向带网)	48	220	1200	46	48~96

## YXF 系列圆形管道式通风机 series Circular Duct Fan

圆形管道风机两边可接同规格的通风管道, 同轴向进风, 风机可串联多区域集中通风, 适用于建筑物室内通风换气或管道加压。广泛用于宾馆酒店、百货商场、娱乐场所及民用住宅通风换气。

Feature: centralized ventilation for multi-zone by one fan. Inlet&Outlet: each side can be connected with ducts of the same size;  
Application: indoor ventilation and pipeline pressurization for hotels, shopping malls and buildings.



机号 Model(Nº)	功率 Power(W)	电压 Voltage(V)	转速 Rotation(r/min)	流量 Volume(m³/h)	静压 Static pressure(Pa)	适用面积 Usable Area(m²)	噪声 Noise dB(A)
YXF100	65	220	2500	300	300	12~24	50
YXF125	70	220	2500	400	350	16~32	48
YXF150	80	220	2500	600	400	24~48	50
YXF160	95	220	2500	750	450	30~60	49
YXF200	130	220	2500	950	550	38~76	52
YXF250	150	220	2500	1050	600	42~84	47
YXF315	190	220	2500	1500	700	60~120	51

## JD 系列斜流增压管道风机 series mixed flow duct ventilator

JD系列斜流增压管道风机, 具有低噪音, 大风量和高静压; 有比轴流式和离心式风机更适合大多数通风应用的优点, 在设计方面, 风机中心盒的电机容易安装拆卸及清洗, 在不去除整个风扇或管道的情况下, 可以拆卸电机和扇叶, 在狭窄空间内也方便维护。在安装方面, 风机可并联或串联且不限角度任意安装, 使用非常灵活, 在管道气体输送中的增压与加压部分得到广泛应用。

JD series mixed flow duct ventilator, has the advantages of low noise, large air flow and high static pressure, it is more suitable for most ventilation situations comparing with axial fan and centrifugal fan. It is design with a simple structure, the motor within the centre box is designed with easy installation, disassembling and cleaning. The design makes it easy to remove the motor and blades without remove the whole fan or any pipelines, or even maintenance or adjust the fan within a sealed space. The installation is also very flexible, it can be installed in parallel or in series or in any angle you need, this fan is wisely used in deliver the gas and enlarge the pressure within the pipe line.



机号 Model(Nº)	功率 Power(W)	电压 Voltage(V)	流量 Volume(m³/h)	全压 Pressure(Pa)	接管直径 Take-Over diameter(mm)
JD100	28/25	220	200/150	180/130	100/125
JD150	50/40	220	500/400	300/250	150/160
JD200	70/60	220	850/700	350/280	200
JD250	170/130	220	1500/1100	550/400	250
JD315	320/230	220	2300/1800	700/500	315