

4-2 × 79 | 型双进风离心通风机

double-suction type centrifugal fan



4-2 × 79型E式双进风离心通风机可用于一般工厂及大型建筑物、空调机组、高层建筑的室内通风换气，既可输入气体，也可输出气体，输送气体为空气和其他不自燃、对人体无害、无腐蚀性气体。气体内不许有粘性物质，所含的尘土及硬质颗粒物 $\leq 150\text{mg}/\text{m}^3$ ，气体温度不得超过 $\leq 80^\circ\text{C}$ 。

This product is use for indoor ventilation in factories, air-condition unit, tall and large buildings, which can not only supply but also discharge gases. The transporting medium is air or other non-spontaneous-combustion and non-explosive-combustion air with no harm to human. The air transferred shall not contain any adhesive material, dust and grain and the concentration shall not exceed $150\text{mg}/\text{m}^3$, with the temperature no higher than 80°C .

机号 Model(Ne)	功率 Power(kW)	转速 Rotation(r/min)	流量 Volume(m ³ /h)	全压 Pressure(Pa)
5E	2.2	1200	6380~11640	618~412
	4	1350	7980~13340	774~480
	5.5	1550	9620~15320	1010~647
	7.5	1800	9850~17160	1382~941
6E	11	2000	13600~18820	1607~1206
	5.5	1200	10990~20070	882~588
	11	1400	12890~23490	1215~814
	15	1650	15190~27000	1676~1186
7E	18.5	1800	16760~29820	1990~1362
	7.5	900	14000~27180	627~473
	11	1000	15570~30240	774~461
	11	1120	17370~33840	970~549
8E	15	1250	19470~37710	1206~716
	30	1600	24930~48330	1970~1166
	11	900	19360~37600	785~471
	15	1000	21520~41680	971~579
9E	22	1120	24080~46720	1226~697
	30	1270	23760~52960	1570~932
	11	740	22664~44019	671~403
	15	800	24502~47588	784~471
10E	18.5	910	27871~54131	1015~609
	30	1060	32465~63054	1377~826
	37	1150	35222~68407	1621~973
	11	580	34320~56600	520~353
12E	15	660	39000~64400	667~461
	18.5	740	43800~72200	843~579
	30	830	49100~81000	1059~726
	37	940	55700~91800	1363~932
14E	15	520	53300~87800	603~402
	22	580	59400~97800	755~510
	37	680	69700~114800	1040~696
	55	740	75800~124800	1216~824
16E	18.5	420	68100~112400	530~363
	30	520	84400~139000	814~549
	75	660	110600~181800	1402~951
	90	740	120200~217800	1657~1128
18E	30	370	89600~148400	539~373
	55	470	113800~188000	873~598
	90	580	140600~231800	1334~902
	132	660	160200~263800	1726~1177
20E	37	360	124200~205000	647~431
	75	420	145000~239000	883~598
	132	520	179800~296200	1363~932
	160	580	200400~330200	1687~1147
20E	55	330	156600~257200	677~461
	90	420	199200~327400	1089~745
	132	470	222000~367000	1373~932
	200	520	246800~406000	1677~1138

LPF-JD | 静电式油烟净化器

HPF-JD | type Electrostatic Oil Fume Purifier

油烟净化器是去除厨房油烟的专用设备。广泛应用于宾馆、饭店、食堂等厨房油烟净化。静电式油烟净化器严禁用于处理工业油烟，柴油炉具燃烧产生的黑烟或易燃、易爆、易挥发、强腐蚀性气体。

This type of fan is specially used for oil fume purification in the kitchen of hotel, restaurant or canteen. But it is strictly prohibited to be used for purifying the air that is inflammable, explosive, volatile and corrosive, or black smoke produced by diesel while burning.

机号 Model(Ne)	功率 Power(W)	电压 Voltage(V)	处理风量 Volume(m ³ /h)	风阻 Drag(Pa)	进风口内尺寸(宽×高) Inlet and outlet size(mm)	外形尺寸(长×宽×高) Outline dimension(mm)
LPF-JD-2	380	220	2000	<300	406×406	1115×670×620
LPF-JD-4	480	220	4000	<300	536×546	1115×800×760
LPF-JD-6	580	220	6000	<300	621×651	1115×885×865
LPF-JD-8	680	220	8000	<300	661×736	1115×925×950
LPF-JD-10	880	220	10000	<300	746×821	1115×1010×1035
LPF-JD-12	980	220	12000	<300	831×884	1115×1095×1098
LPF-JD-14	1080	220	14000	<300	872×1001	1115×1135×1215
LPF-JD-16	1180	220	16000	<300	916×1071	1115×1180×1285
LPF-JD-18	1280	220	18000	<300	960×1171	1115×1224×1385
LPF-JD-20	1450	220	20000	<300	960×1171	1115×1224×1385

机号 Model(Ne)	功率 Power(W)	电压 Voltage(V)	处理风量 Volume(m ³ /h)	风阻 Drag(Pa)	进风口内尺寸(宽×高) Inlet and outlet size(mm)	外形尺寸(长×宽×高) Outline dimension(mm)
HPF-JD-2	200	220	2000	<150	406×406	1115×670×620
HPF-JD-4	300	220	4000	<150	536×546	1115×800×760
HPF-JD-6	400	220	6000	<150	621×651	1115×885×865
HPF-JD-8	500	220	8000	<150	661×736	1115×925×950
HPF-JD-10	650	220	10000	<150	746×821	1115×1010×1035
HPF-JD-12	800	220	12000	<150	831×884	1115×1095×1098
HPF-JD-14	900	220	14000	<150	872×1001	1115×1135×1215
HPF-JD-16	1000	220	16000	<150	916×1071	1115×1180×1285
HPF-JD-18	1100	220	18000	<150	960×1171	1115×1224×1385
HPF-JD-20	1250	220	20000	<150	960×1171	1115×1224×1385



HPF-JD型(高排)



LPF-JD型(低排)



内部结构